

# K-SPIR SCHL

Spiral hose, without fittings

## Lastnosti

**Uporaba** Air, gases, oils, greases, fuels, organic and inorganic substances

**delovna temperatura** -40 °C to +100 °C



## Navodilo

Drugi podatki na zahtevo.

## Opis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Artikel

Opis	Ø cevi znotraj (mm)	Ø cevi zunaj (mm)	Ø spirale zunaj (mm)	navitja	Max. working pressure resistance at 23°C (bar)	maks. delovna dolžina (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

## Pribor

**K-DREHBARE VERSCHR KNICK** Swivel adapters with kink protector

**K-STARRE VERSCHRAUBUNG** Rigid adapters with kink protector