

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Lastnosti

vrsta priključka with kink protector, swivel type

delovna temperatura -40 °C to +74 °C



## Navodilo

Drugi podatki na zahtevo.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Artikel

Opis	Navoj	Ø cevi znotraj (mm)	Ø cevi zunaj (mm)	Ø zunanje navitje (mm)	Max. working pressure resistance at 23°C (bar)	maks. delovna dolžina (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

## Pribor

K-DREHBARE VERSCHRAUBUNG Swivel adapters