

## Lastnosti

ohišje	Amaplast with hinged cover
vgrajeno v ohišje	Hanging eyelets, wall mounting fixing and standing feet
varovalo	Beneath transparent lid (4 MW)
Izvedba	Pre-wired
uvodnice za napeljavo	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
razred zaščite	IP 44



## Navodilo

Drugi podatki na zahtevo.

## Opis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

## Artikel

Opis	namestitvev	Barva
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	rumeno
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	srebrna

## Pribor

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«