

K-VSEH AIRKRAFT

Receptacle combinations »airkraft«

HANSA FLEX

Lastnosti

ohišje	Amaplast with hinged cover
vgrajeno v ohišje	Hanging eyelets, wall mounting fixing and standing feet
varovalo	Beneath transparent lid (4 MW)
Izvedba	Pre-wired
uvodnice za napeljavo	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
razred zaščite	IP 44



Navodilo

Drugi podatki na zahtevo.

Opis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Artikel

Opis	namestitvev	Barva
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	rumeno
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	srebrna

Pribor

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«