

# K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

**HANSA FLEX**

## Lastnosti

|  |   |
|--|---|
| <b>Obratovalni tlak</b>                    | See table. All values referred to a medium temperature of 50 °C (static working pressure)   |
| <b>pretok zraka</b>                        | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| <b>temperatura medija</b>                  | -20 °C to +90 °C  |
| <b>ohišje, puša</b>                        | POM (Delrin), white   |
| <b>ventil</b>                              | Stainless steel 1.4305  |
| <b>vzmet, notranji zaskočnik, kroglice</b> | stain less steel  |
| <b>tesnilni material</b>                   | NBR   |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artikel

| Opis                  | Priključek   | Obratovalni tlak (bar) | dolžina (mm) | nazivni premer | SW (mm) |
|-----------------------|--------------|------------------------|--------------|----------------|---------|
| <b>K- 07 35 03 76</b> | G 1/8 female | 15,0                   | 48,5         | 4,3            | 14      |
| <b>K- 07 35 03 77</b> | G 1/4 female | 15,0                   | 57,6         | 6,0            | 19      |
| <b>K- 07 35 03 78</b> | G 3/8 female | 15,0                   | 64,2         | 7,5            | 22      |
| <b>K- 07 35 03 79</b> | G 1/2 female | 10,0                   | 76,0         | 11,0           | 27      |
| <b>K- 07 35 03 80</b> | G 3/4 female | 10,0                   | 96,0         | 13,0           | 34      |