


K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Lastnosti

Obratovalni tlak	See table. All values referred to a medium temperature of 50 °C (static working pressure)
pretok zraka	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
temperatura medija	-20 °C to +90 °C
ohišje, puša	POM (Delrin), white
ventil	Stainless steel 1.4305
vzmet, notranji zaskočnik, krogla	stain less steel
tesnilni material	NBR



Navodilo

Drugi podatki na zahtevo.

Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artikel

Opis	Priključek	Obratovalni tlak (bar)	dolžina (mm)	nazivni premer	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36