

K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Lastnosti

Obratovalni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
pretok zraka	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
temperatura medija	-20 °C to +100 °C
puša za deblokado	Anodised aluminium
vzmet, notranji zaskočnik, kroglice	stain less steel
tesnilni material	NBR



Navodilo

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Drugi podatki na zahtevo.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikel

Opis	Priključek	Barva	dolžina (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zeleno	45,0	14
K- 07 35 06 81	G 1/4 male	zeleno	47,0	17
K- 07 35 06 82	G 1/8 female	zeleno	45,0	14
K- 07 35 06 83	G 1/4 female	zeleno	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	modro	45,0	14
K- 07 35 06 89	G 1/4 male	modro	47,0	17
K- 07 35 06 90	G 1/8 female	modro	45,0	14
K- 07 35 06 91	G 1/4 female	modro	47,0	17
K- 07 35 06 92	G 1/8 male	rdeče	45,0	14
K- 07 35 06 93	G 1/4 male	rdeče	47,0	17
K- 07 35 06 94	G 1/8 female	rdeče	45,0	14
K- 07 35 06 95	G 1/4 female	rdeče	47,0	17