


K-LKS 5 UWB

Stems and plugs DN 5

Lastnosti

Obratovalni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
pretok zraka	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
temperatura medija	-20 °C to +100 °C
Material:	med



Navodilo

Drugi podatki na zahtevo.

Artikel

Opis	definicija	Barva	SW (mm)
K- 07 35 01 54	Stem, I.D. 6	zeleno	-
K- 07 35 01 55	Stem, I.D. 6	Brown	-
K- 07 35 01 56	Stem, I.D. 6	modro	-
K- 07 35 01 57	Stem, I.D. 6	rdeče	-
K- 07 35 01 58	Plug G 1/8 male	zeleno	17
K- 07 35 01 59	Plug G 1/4 male	zeleno	17
K- 07 35 01 60	Plug G 1/8 female	zeleno	17
K- 07 35 01 61	Plug G 1/4 female	zeleno	17
K- 07 35 01 62	Plug G 1/8 male	Brown	17
K- 07 35 01 63	Plug G 1/4 male	Brown	17
K- 07 35 01 64	Plug G 1/8 female	Brown	17
K- 07 35 01 65	Plug G 1/4 female	Brown	17
K- 07 35 01 66	Plug G 1/8 male	modro	17
K- 07 35 01 67	Plug G 1/4 male	modro	17
K- 07 35 01 68	Plug G 1/8 female	modro	17
K- 07 35 01 69	Plug G 1/4 female	modro	17
K- 07 35 01 70	Plug G 1/8 male	rdeče	17
K- 07 35 01 71	Plug G 1/4 male	rdeče	17
K- 07 35 01 72	Plug G 1/8 female	rdeče	17
K- 07 35 01 73	Plug G 1/4 female	rdeče	17