K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Lastnosti



Obratovalni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
pretok zraka	1.800 l/min (at 6 bar and Δp = 0.5 bar)
temperatura medija	-20 °C to +100 °C
ohišje	Brass
ventil	Die-cast zinc, nickel-plated
puša za deblokado	Anodised aluminium
vzmet, notranji zaskočnik, krogle	stain less steel
tesnilni material	NBR

Navodilo

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Drugi podatki na zahtevo.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikel

Opis	Priključek	Barva	dolžina (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	zeleno	57,5	19
K- 07 35 08 02	G 3/8 male	zeleno	57,5	19
K- 07 35 08 03	G 1/4 female	zeleno	55,5	19
K- 07 35 08 04	G 3/8 female	zeleno	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	modro	57,5	19
K- 07 35 08 10	G 3/8 male	modro	57,5	19
K- 07 35 08 11	G 1/4 female	modro	55,5	19
K- 07 35 08 12	G 3/8 female	modro	54,5	19
K- 07 35 08 13	G 1/4 male	rdeče	57,5	19
K- 07 35 08 14	G 3/8 male	rdeče	57,5	19
K- 07 35 08 15	G 1/4 female	rdeče	55,5	19
K- 07 35 08 16	G 3/8 female	rdeče	54,5	19

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.