


# K-LKS 7,8 UWB

## Stems and plugs DN 7.8

### Lastnosti

Obratovalni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
pretok zraka	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
temperatura medija	-20 °C to +100 °C
Material:	med



### Navodilo

Drugi podatki na zahtevo.

### Artikel

Opis	definicija	Barva	SW (mm)
K- 07 35 02 71	Stem, I.D. 6	zeleno	-
K- 07 35 02 72	Stem, I.D. 9	zeleno	-
K- 07 35 02 73	Stem, I.D. 6	Brown	-
K- 07 35 02 74	Stem, I.D. 9	Brown	-
K- 07 35 02 75	Stem, I.D. 6	modro	-
K- 07 35 02 76	Stem, I.D. 9	modro	-
K- 07 35 02 77	Stem, I.D. 6	rdeče	-
K- 07 35 02 78	Stem, I.D. 9	rdeče	-
K- 07 35 02 79	Plug G 1/4 male	zeleno	17
K- 07 35 02 80	Plug G 3/8 male	zeleno	19
K- 07 35 02 81	Plug G 1/4 male	Brown	17
K- 07 35 02 82	Plug G 3/8 male	Brown	19
K- 07 35 02 83	Plug G 1/4 male	modro	17
K- 07 35 02 84	Plug G 3/8 male	modro	19
K- 07 35 02 85	Plug G 1/4 male	rdeče	17
K- 07 35 02 86	Plug G 3/8 male	rdeče	19