

K-KOMPAKTEJEKTOREN MINI

Mini-compact ejectors

HANSA FLEX

Lastnosti

Lastnosti

- Vacuum generator with integrated control valves and system monitoring functions
- Gripping and blowing off can be controlled without the need for external valves
- Optimised air consumption thanks to many models with differing suction capacities
- Minimum energy costs in continuous operation
- Easy adjustment with foil keypad, LED display of the settings
- Minimum size and low weight
- Optimum vacuum generation directly on the suction pad
- Complete solution for very simple installation
- Short learning curve thanks to "teach" function
- No need for additional sensors
- Easily visible status indication


Uporaba

Ideal where space is restricted and for highly dynamic movements, handling with industrial robots, linear axes pick-and-place systems

stopnja praznjenja 85 %

osnovno ohišje Anodised aluminium

integrirano NC blow-off valve, filter, silencer, non-return valve



Navodilo

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Drugi podatki na zahtevo.

Opis

Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Dodatne informacije

Important: Order two connection plugs per ejector.

Artikel

| Opis | velikost šobe | mirujoči položaj sesalnega ventila | priključek za stisnjen zrak | vakuumski priključek | poraba zraka za sesanje (L/min) | maks. sesalna zmogljivost (L/min) | Mera | Obratovalni tlak (bar) |
|----------------|---------------|------------------------------------|-----------------------------|----------------------|---------------------------------|-----------------------------------|---------------------|------------------------|
| K- 07 45 01 46 | 1,0 | NC | M 5 IG | M5 female | 46,0 | 23,0 | 65mm x 10mm x 107mm | 4,5 |
| K- 07 45 01 45 | 1,0 | NO | M 5 IG | M5 female | 46,0 | 23,0 | 65mm x 10mm x 107mm | 4,5 |

Pribor

K-ANSCHLUSSSTECK MAGNETVE 1 Connection plug for solenoid valves

K-ERSATZSCHALLDAEMPFER Replacement silencers

K-ERSATZFILTERELEMENTE 1 Replacement filter element