

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Lastnosti

Uporaba	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatura min.	0 °C
Temperatura max.	80 °C
priključek sesalnika	M 3 female
Izvedba	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
gib vzmeti	5,0 mm



Navodilo

Drugi podatki na zahtevo.

Opis

Suitable for all round or oval suction pads in our standard range.

Artikel

Opis	vakuumski priključek	dolžina (mm)	navpična obremenitev (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400