

K-DRS

Pressure switch

Lastnosti

| | |
|-----------------------------|---|
| priključek za merjeni medij | G 1/8 male and M 5 female |
| izhodni signal | 2 x digital |
| Način izdelave | PNP |
| Električni priključek | Male connector M8, four pin |
| histereza | Adjustable: 0 to 100% of set value or comparator mode |
| Sredstva | Non-aggressive gases. dry, oil-free air |
| prikaz merilne vrednosti | 3-digit 7-segment LED |
| zmogljivost stikala | 180 mA |
| potrebni tok | 55 mA |
| območje temperatur: | 0 - 50 °C |
| ohišje | Polycarbonate |
| prikaz stanja | 2 x LED |



Navodilo

Drugi podatki na zahtevo.

Opis

Universal electronic pressure switch for safety monitoring, optimisation of cycle times and regulation circuits.
Its small size and low weight permit installation in handling systems directly at the point of use.

Artikel

| Opis | G1 zunaj | G2 znotraj | G3 zunaj | L (mm) | L1 (mm) | Mersko območje | Napetost |
|----------------|----------|------------|----------|--------|---------|----------------|----------------|
| K- 07 45 01 32 | G 1/8 | M 5 | M 8 x 1 | 58,5 | 75,5 | 0 - 10 bar | 10.8 - 30 V DC |