


K-DRUCKSCHALTER VAKUUM

Combined vacuum/pressure switch

HANSA FLEX

Lastnosti

| | |
|-----------------------------|---|
| Način izdelave | PNP |
| priključek za merjeni medij | G 1/8 male and M 5 female |
| histereza | Adjustable: 3 to 25% of set value |
| območje temperatur: | 0 - 50 °C |
| Sredstva | Non-aggressive gases. dry, oil-free air |
| ohišje | Polycarbonate |
| izhodni signal | Analogue: 1 to 5 V |
| Električni priključek | Male connector M8, four pin |
| zmogljivost stikala | 125 mA |
| potrebni tok | 30 mA |
| prikaz stanja | LED |



Navodilo

Drugi podatki na zahtevo.

Opis

Universal electronic vacuum and pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly at the point of use. Suitable for all special applications in the vacuum and compressed air sectors. Adjustable vacuum limit value and continuous vacuum monitoring.

Artikel

| Opis | G1 zunaj | G2 znotraj | G3 zunaj | L (mm) | L1 (mm) | Mersko območje | Napetost |
|----------------|----------|------------|----------|-----------|------------|----------------|----------------|
| K- 07 45 01 31 | G 1/8 | M 5 | M 8 x 1 | 44,0 | 62,0 | -1 bis +10 bar | 10.8 - 30 V DC |