# K-SNV ABSP V MS CR

Quick-stop shut-off valves, chrome-plated brass

## Lastnosti

| | |
|---|---|
| **Uporaba** | Fuel oil, liquefied gas (in gas phase), compressed air |
| **Obratovalni tlak** | max. 16 bar for valves with cutting ring connection; max. 4 bar for valves with pipe thread |
| **opis navoja** | G thread acc. DIN EN ISO 228-1 |
| **ohišje** | |



## Navodilo

Drugi podatki na zahtevo.

## Artikel

| Opis | DN | Priključek |
|---|---|---|
| **K- 07 30 30 91** | 7 | G 1/4 female thread |
| **K- 07 30 30 92** | 8 | G 3/8 female thread |
| **K- 07 30 30 93** | 12 | G 1/2 female thread |
| **K- 07 30 30 94** | 4 | 6 mm pipe |
| **K- 07 30 30 95** | 6 | 8 mm pipe |
| **K- 07 30 25 22** | 7 | 10 mm pipe |
| **K- 07 30 30 96** | 10 | 12 mm pipe |
| **K- 07 30 25 23** | 12 | 15 mm pipe |

*Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.*