

# K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

**HANSA FLEX**

## Lastnosti

temperatura medija	-5 °C to +80 °C
maks. izklopni tlak	16 bar
zmogljivost stikala	5,5 kW
vrsta kontaktov	NC (3-pole)
maks. pogostost preklopa	120 (electrical), 600 (mechanical)
razred zaščite	IP 54



## Navodilo

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Drugi podatki na zahtevo.

## Opis

Three-phase version

## Navodila za naročanje

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Dodatne informacije

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Artikel

Opis	priključek za stisnjen zrak	območje nastavitve
K- 07 30 24 24	G 1/2	2,0 - 11,0 bar
K- 07 30 24 26	G 1/2	2,5 - 16,0 bar