

K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

HANSA FLEX

Lastnosti

| | |
|--------------------------|------------------------------------|
| temperatura medija | -5 °C to +80 °C |
| maks. izklopni tlak | 16 bar |
| zmogljivost stikala | 5,5 kW |
| vrsta kontaktov | NC (3-pole) |
| maks. pogostost preklopa | 120 (electrical), 600 (mechanical) |
| razred zaščite | IP 54 |



Navodilo

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Drugi podatki na zahtevo.

Opis

Three-phase version

Navodila za naročanje

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatne informacije

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Artikel

| Opis | priključek za stisnjen zrak | območje nastavitve |
|----------------|-----------------------------|--------------------|
| K- 07 30 24 25 | G 1/2 | 2,0 - 11,0 bar |
| K- 07 30 24 27 | G 1/2 | 2,5 - 16,0 bar |