

# K-DRS W BAJONETT

## Pressure switches - changeover type

### Lastnosti

|                                |   |
|--------------------------------|---|
| <b>Način izdelave</b>          | Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions) |
| <b>temperatura okolice</b>     | -25 °C to +85 °C  |
| <b>Električni priključek</b>   | Bayonet coupling connector Ø 2.5 mm   |
| <b>pogostost preklapljanja</b> | 200/min.  |
| <b>merilna napetost</b>        | 42 V  |
| <b>funkcija</b>                | Changeover  |
| <b>Material:</b>               | Galvanised steel  |



### Navodilo

Drugi podatki na zahtevo.

### Opis

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

### Artikel

| Opis           | Navoj | območje nastavitve |
|----------------|-------|--------------------|
| K- 07 30 28 36 | G 1/8 | 0,5 - 2,0 bar      |
| K- 07 30 28 37 | G 1/8 | 1,0 - 10,0 bar     |
| K- 07 30 28 38 | G 1/8 | 10,0 - 70,0 bar    |
| K- 07 30 28 39 | G 1/4 | 0,5 - 2,0 bar      |
| K- 07 30 28 40 | G 1/4 | 1,0 - 10,0 bar     |
| K- 07 30 28 41 | G 1/4 | 10,0 - 70,0 bar    |

### Pribor

**K-WECHSELKONTAKT BANJOETT** Changeover type bayonet coupling