

K-DRS W BAJONETT

Pressure switches - changeover type

Lastnosti

| | |
|--------------------------------|---|
| Način izdelave | Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions) |
| temperatura okolice | -25 °C to +85 °C |
| Električni priključek | Bayonet coupling connector Ø 2.5 mm |
| pogostost preklapljanja | 200/min. |
| merilna napetost | 42 V |
| funkcija | Changeover |
| Material: | Galvanised steel |



Navodilo

Drugi podatki na zahtevo.

Opis

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

Artikel

| Opis | Navoj | območje nastavitve |
|----------------|-------|--------------------|
| K- 07 30 28 36 | G 1/8 | 0,5 - 2,0 bar |
| K- 07 30 28 37 | G 1/8 | 1,0 - 10,0 bar |
| K- 07 30 28 38 | G 1/8 | 10,0 - 70,0 bar |
| K- 07 30 28 39 | G 1/4 | 0,5 - 2,0 bar |
| K- 07 30 28 40 | G 1/4 | 1,0 - 10,0 bar |
| K- 07 30 28 41 | G 1/4 | 10,0 - 70,0 bar |

Pribor

K-WECHSELKONTAKT BANJOETT Changeover type bayonet coupling