

# K-SCHLAUCHBRUCHSICHERUNG

Hose rupture valves Typ Hose Guard

**HANSA FLEX**

## Lastnosti

|                     |   |
|---------------------|---|
| ohišje              | Aluminium   |
| bat                 | Polyacetate (G 1/4 to G 1/2); Aluminium (G 3/4 to G 2)  |
| Tesnilni obroč      | NBR   |
| maks. vstopni tlak  | 18 bar (G 1/4 to G 3/4); 35 bar (G 1 to G 2)  |
| območje temperatur: | -20 °C to +80 °C (G 1/4 to G 1/2)<br>-20 °C to +120 °C (G 3/4 to G 2)   |
| vgradnja            | Upstream of a coupling (connector between hard piping and junction box/coupling) and downstream of a service unit |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Efficient protection for ruptured hoses or pipes in pneumatic systems. Preset to permit normal air consumption by pneumatic tools. Hose Guard detects a rupture in a hose or pipe and interrupts the supply of compressed air in a fraction of a second apart from a minimal residual flow. Unaffected parts of the compressed air system remain fully pressurised, so that the damaged hose or segment can be replaced without difficulty. Once the ruptured hose or pipe has been repaired, the replaced segment gradually fills to its working pressure level. As soon as this occurs, Hose Guard opens the line again for normal operation. Hose Guard protects personnel, machinery and plant against damage if a pneumatic system or hose ruptures, complies with the EU standard DIN EN ISO 4414: 2010, 2011-04 - § 5.4.5.11, is reliable and tamper-proof, can be installed in any pneumatic system, bears the TÜV test mark 01-02-0145.

## Navodila za naročanje

ATTENTION: For suitable hoses, please check the respective data sheet.

## Artikel

| Opis           | Navoj                 | SW<br>(mm) | dolžina<br>(mm) |
|----------------|-----------------------|------------|-----------------|
| K- 07 30 24 84 | G 1/4 male/female     | 22         | 57,0            |
| K- 07 30 24 86 | G 3/8 male/female     | 27         | 76,0            |
| K- 07 30 24 83 | G 1/2 male/female     | 30         | 80,0            |
| K- 07 30 24 88 | G 1/4 female/female   | 22         | 48,0            |
| K- 07 30 24 90 | G 3/8 female / female | 27         | 59,0            |
| K- 07 30 24 87 | G 1/2 female/female   | 30         | 65,0            |
| K- 07 30 24 89 | G 3/4 female/female   | 36         | 76,0            |
| K- 07 30 24 82 | G 1 female/female     | 50         | 100,0           |
| K- 07 30 24 85 | G 2 female/female     | 80         | 130,0           |