


# K-T-STUECKE IG IG AG 2 2

Tees, female-female-male

**HANSA FLEX**

## Lastnosti

|                     |                                 |
|---------------------|---------------------------------|
| Obratovalni tlak    | 60 bar                          |
| delovna temperatura | Max. 150 °C                     |
| notranji navoj      | Parallel to DIN EN ISO 228-1    |
| Material:           | Brass with a bare metal surface |
| zunanji navoj       | conical acc. DIN 2999           |



## Navodilo

Drugi podatki na zahtevo.

## Artikel

| Opis           | Navoj   | L1<br>(mm) | L2<br>(mm) | zev ključa |
|----------------|---------|------------|------------|------------|
| K- 07 40 11 70 | G/R 1/8 | 39,5       | 21,0       | 10 mm      |
| K- 07 40 11 71 | G/R 1/4 | 49,0       | 23,5       | 13 mm      |
| K- 07 40 11 72 | G/R 3/8 | 54,0       | 28,0       | 17 mm      |
| K- 07 40 11 73 | G/R 1/2 | 64,5       | 33,5       | 21 mm      |
| K- 07 40 11 74 | G/R 3/4 | 69,5       | 36,5       | 25 mm      |
| K- 07 40 11 75 | G/R 1   | 84,0       | 45,0       | 30 mm      |