

K-W90 AG-K

Male elbows, conical male thread

HANSA FLEX

Lastnosti

| | |
|---------------------|--|
| Obratovalni tlak | Max. 16 bar (at +20 °C) |
| delovna temperatura | -20 °C to +70 °C |
| Material: | ponikljana medenina |
| potisni obroč | Hostaform (black nickel-plated for Ø 10, 12) |
| tesnilni obroč | NBR, siliconefree |
| vpenjalne klešče | Stainless steel AISI 316 |



Navodilo

Drugi podatki na zahtevo.

Opis

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Artikel

| Opis | Navoj | za zunanji Ø mm cevi | L1 (mm) | L2 (mm) | zev ključa |
|----------------|-------|----------------------|------------|------------|------------|
| K- 07 40 29 65 | R 1/8 | 4 mm | 16,1 | 17,5 | 10 mm |
| K- 07 40 29 66 | R 1/8 | 6 mm | 20,0 | 17,5 | 10 mm |
| K- 07 40 29 67 | R 1/8 | 8 mm | 24,0 | 18,5 | 10 mm |
| K- 07 40 29 63 | R 1/4 | 6 mm | 23,0 | 22,0 | 12 mm |
| K- 07 40 29 64 | R 1/4 | 8 mm | 24,0 | 22,0 | 12 mm |
| K- 07 40 29 62 | R 1/4 | 10 mm | 24,0 | 22,0 | 14 mm |