

# K-W90 VERBINDER POM

Union elbows

**HANSA FLEX**

## Lastnosti

|                     |   |
|---------------------|---|
| delovni tlak        | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)    |
| delovna temperatura | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| Material:           | Acetalpolymerisat (POM)                           |
| tesnilni material   | NBR   |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

## Artikel

| Opis           | za zunanji Ø mm cevi | L1<br>(mm) | L2<br>(mm) |
|----------------|----------------------|------------|------------|
| K- 07 40 28 52 | 4 mm                 | 25,1       | 25,1       |
| K- 07 40 28 53 | 5 mm                 | 25,1       | 25,1       |
| K- 07 40 28 54 | 6 mm                 | 28,1       | 28,1       |
| K- 07 40 28 55 | 8 mm                 | 30,9       | 30,9       |
| K- 07 40 28 56 | 10 mm                | 36,2       | 36,2       |
| K- 07 40 28 57 | 12 mm                | 45,0       | 45,0       |
| K- 07 40 28 58 | 15 mm                | 51,4       | 51,4       |
| K- 07 40 28 59 | 18 mm                | 60,9       | 60,9       |
| K- 07 40 28 60 | 22 mm                | 67,4       | 67,4       |
| K- 07 40 28 61 | 28 mm                | 87,7       | 87,7       |