


# K-TR AG-K MS NI

Male hose fittings, conical male thread - nickel-plated brass

**HANSA FLEX**

## Lastnosti

|                     |                     |
|---------------------|---------------------|
| delovna temperatura | Max. 150 °C         |
| tlak                | Max. 60 bar         |
| Material:           | ponikljana medenina |



## Navodilo

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Drugi podatki na zahtevo.

## Opis

Suitable for air, water, oil, steam, etc.

## Dodatne informacije

Further types and dimensions on request.

## Artikel

| Opis           | Navoj | za cev   | L1 (mm) | L2 (mm) | zev ključa |
|----------------|-------|----------|---------|---------|------------|
| K- 07 40 13 44 | R 1/8 | LW 6 mm  | 31,5    | 8,0     | 12 mm      |
| K- 07 40 13 45 | R 1/8 | LW 8 mm  | 31,5    | 8,0     | 12 mm      |
| K- 07 40 13 46 | R 1/8 | LW 9 mm  | 31,5    | 8,0     | 12 mm      |
| K- 07 40 13 47 | R 1/8 | LW 10 mm | 32,5    | 8,0     | 12 mm      |
| K- 07 40 13 48 | R 1/4 | LW 6 mm  | 35,0    | 11,0    | 14 mm      |
| K- 07 40 13 49 | R 1/4 | LW 8 mm  | 35,0    | 11,0    | 14 mm      |
| K- 07 40 13 50 | R 1/4 | LW 9 mm  | 35,0    | 11,0    | 14 mm      |
| K- 07 40 13 51 | R 1/4 | LW 10 mm | 36,0    | 11,0    | 14 mm      |
| K- 07 40 13 52 | R 1/4 | LW 12 mm | 36,0    | 11,0    | 14 mm      |
| K- 07 40 49 75 | R 1/4 | LW 13 mm | 39,5    | 11,5    | 14 mm      |
| K- 07 40 13 53 | R 3/8 | LW 9 mm  | 35,5    | 11,5    | 17 mm      |
| K- 07 40 13 54 | R 3/8 | LW 10 mm | 36,5    | 11,5    | 17 mm      |
| K- 07 40 13 55 | R 3/8 | LW 12 mm | 36,5    | 11,5    | 17 mm      |
| K- 07 40 49 77 | R 3/8 | LW 13 mm | 41,0    | 13,0    | 17 mm      |
| K- 07 40 13 56 | R 1/2 | LW 9 mm  | 38,5    | 14,0    | 22 mm      |
| K- 07 40 13 57 | R 1/2 | LW 10 mm | 39,5    | 14,0    | 22 mm      |
| K- 07 40 13 58 | R 1/2 | LW 12 mm | 39,5    | 14,0    | 22 mm      |
| K- 07 40 49 78 | R 1/2 | LW 13 mm | 44,5    | 15,5    | 22 mm      |
| K- 07 40 49 79 | R 1/2 | LW 16 mm | 44,5    | 15,5    | 22 mm      |
| K- 07 40 49 80 | R 1/2 | LW 19 mm | 44,5    | 15,5    | 22 mm      |