


# K-SCHWENKTUELLE MS

Swivel hose fittings, parallel male thread

**HANSA FLEX**

## Lastnosti

|                     |   |
|---------------------|---|
| delovni tlak        | 10 bar  |
| temperatura medija  | max. +90 °C   |
| temperatura okolice | Max. +90 °C   |
| Material:           | Nickel-plated brass (banjo bolt), brass (ring nipple) |



## Navodilo

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Drugi podatki na zahtevo.

## Dodatne informacije

Further types and dimensions on request.

## Artikel

| Opis           | Navoj | za cev  | L1<br>(mm) | L2<br>(mm) | zev ključa |
|----------------|-------|---------|------------|------------|------------|
| K- 07 40 34 39 | G 1/8 | LW 4 mm | 26,0       | 28,0       | 14 mm      |
| K- 07 40 34 40 | G 1/8 | LW 6 mm | 26,0       | 28,0       | 14 mm      |
| K- 07 40 34 41 | G 1/4 | LW 6 mm | 28,0       | 29,0       | 17 mm      |
| K- 07 40 34 42 | G 1/4 | LW 9 mm | 28,0       | 30,5       | 17 mm      |
| K- 07 40 34 43 | G 3/8 | LW 6 mm | 30,0       | 32,0       | 22 mm      |
| K- 07 40 34 44 | G 3/8 | LW 9 mm | 30,0       | 32,0       | 22 mm      |