K-KONDENSA DRUKODRAIM PLUS

Drain for compressed air condensate

Lastnosti

priključna moč filtra	100 m3/min
priključna moč kompresorja	10 m3/min
priključna moč sušilnika	20 m3/min



Navodilo

Drugi podatki na zahtevo.

Opis

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

Navodila za naročanje

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

Artikel

Opis	Obratovalni tlak bar	Napetost
K- 07 25 09 24	0.2 - 16 bar	230 VAC / 50 Hz

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.