
## K-PROP VENTIL LU GA WA 24 V DC

Proportional valves for controlling the flow of air / gas / water / oil, 24 VDC, closed when de-energised



Lastnosti					
območje temperatur:	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)				
Sredstva	Air, neutral gases, water, oil				
tlačno območje	Vacuum (max. 8 bar)				
krmiljenje	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA				
vedenje Failsafe	Tight closure in case of loss of voltage				
ohišje, sedež ventila	Brass				
notranji deli	Stainless steel				
krožnik ventila	FKM				
tesnilni material	FKM				





## Navodilo

Drugi podatki na zahtevo.

## Opis

## Dodatne informacije

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Artikel						
Opis	Priključek	DN	maks. delovna tlačna razlika	A (mm)	В	C (mm)
K- 07 25 09 89	G 1/8	1	5	59,0	25,0 mm	78,0
K- 07 25 09 90	G 1/8	2	4	59,0	25,0 mm	78,0