
K-PROP VENTIL WA 24 V DC

Proportional valves for controlling the flow of water / oil, 24 VDC, closed when de-energised



Lastnosti					
območje temperatur:	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)				
Sredstva	Air, neutral gases, water, oil				
tlačno območje	Vacuum (max. 8 bar)				
krmiljenje	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA				
vedenje Failsafe	Tight closure in case of loss of voltage				
ohišje, sedež ventila	Brass				
notranji deli	Stainless steel				
krožnik ventila	FKM				
tesnilni material	FKM				





Navodilo

Drugi podatki na zahtevo.

Opis

Dodatne informacije

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Artikel								
Opis	Priključek	DN	maks. delovna tlačna razlika (bar)	A (mm)	В	C (mm)		
K- 07 25 09 95	G 1/4	2	8	85,0	40,0 mm	95,0		
K- 07 25 09 96	G 1/4	3	4	85,0	40,0 mm	95,0		
K- 07 25 09 97	G 3/8	6	1	85,0	48,0 mm	97,0		
K- 07 25 09 98	G 3/8	7	1	85,0	48,0 mm	97,0		