

K-FLASCHENDRUCKR 200 N GASE

regulator tlaka v jeklenki, tlak v jeklenki 200 bar, za negorljive pline


HANSA FLEX

Lastnosti

manometer za vsebino 0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene

Material: zatisna medenina

priključek za steklenice Nut 3/4



Navodilo

Drugi podatki na zahtevo.

Opis

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Artikel

| Opis | vrsta plina | Obratovalni tlak bar |
|----------------|----------------|----------------------|
| K- 07 25 07 11 | Oxygen | 0 - 10,0 bar |
| K- 07 25 07 12 | Oxygen | 0 - 20,0 bar |
| K- 07 25 07 14 | Compressed air | 0 - 10,0 bar |
| K- 07 25 07 15 | Compressed air | 0 - 20,0 bar |
| K- 07 25 07 16 | Nitrogen | 0 - 10,0 bar |
| K- 07 25 07 17 | Nitrogen | 0 - 20,0 bar |
| K- 07 25 07 18 | Carbon dioxide | 0 - 10,0 bar |
| K- 07 25 07 19 | Carbon dioxide | 0 - 20,0 bar |
| K- 07 25 07 20 | Argon/helium | 0 - 10,0 bar |

Nadomestni deli

| | |
|-------------------------|-----------------------------|
| K-MANO SCHWEISSTECHNIK | Content pressure gauge |
| K-MANO SCHW | Pressure gauges for welding |
| K-SCHUTZKAPPE MANOMETER | zaščitne kape |