

# K-FLASCHENDRUCKR 300 N GASE

regulator tlaka v jeklenki, tlak v jeklenki 300 bar, za negorljive pline


**HANSA FLEX**

## Lastnosti

**manometer za vsebino** 0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene

**Material:** zatisna medenina

**priključek za steklenice** W 30 x 2



## Navodilo

Drugi podatki na zahtevo.

## Opis

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

## Artikel

Opis	vrsta plina	Obratovalni tlak bar
K- 07 25 07 22	Oxygen	0 - 10,0 bar
K- 07 25 07 23	Compressed air	0 - 10,0 bar
K- 07 25 07 24	Nitrogen	0 - 10,0 bar
K- 07 25 07 25	Nitrogen	0 - 20,0 bar

## Nadomestni deli

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	zaščitne kape