


K-PRAEZI DRUCKREGL MEM SELU

Precision pressure regulators

HANSA FLEX

Lastnosti

| | |
|--------------------------------|--|
| vstopni tlak | Max. 16 bar |
| temperatura medija | max. 60 °C |
| temperatura okolice | Max. 60 °C |
| Sredstva | Micro-filtered, unoiled compressed air (0.01 µm) |
| priključek za manometer | G 1/8 |
| tesnilni material | NBR |
| ohišje | Die-cast zinc |
| lastna poraba zraka | 2.2 - 4.5 l/min, depending on input pressure and control range |



Navodilo

The given flow rates are based on the following parameters: 450 l/min: P1: 5 bar, P2: 2 bar, $\Delta p \leq 0.1$ bar

570 l/min: P1: 7 bar, P2: 4 bar, $\Delta p \leq 0.1$ bar

Attention! Wear parts kit not supplied! Pressure regulator may only be opened in the factory! 850 l/min: P1: 10 bar, P2: 7 bar, $\Delta p \leq 0.1$ bar.

Drugi podatki na zahtevo.

Opis

Diaphragm pressure regulators with self-relieving design for applications requiring an extremely accurate working pressure.

Dodatne informacije

1500 l/min: P1: 10 bar, P2: 7 bar, $\Delta p \leq 0.1$ bar.

Artikel

| Opis | Navoj | regulacijsko območje | pretok (L/min) | A (mm) | B | C (mm) | D (mm) |
|-----------------------|-------|----------------------|----------------|--------|----------|--------|--------|
| K- 07 25 09 43 | G 1/4 | 0.05 - 2 bar | 450 | 58,0 | 124,0 mm | 107,0 | 17,0 |
| K- 07 25 09 44 | G 1/4 | 0.05 - 4 bar | 570 | 58,0 | 124,0 mm | 107,0 | 17,0 |
| K- 07 25 09 45 | G 1/4 | 0.05 - 7 bar | 850 | 58,0 | 124,0 mm | 107,0 | 17,0 |

Nadomestni deli

| | |
|------------------------|--------------------------------------|
| K-HALTERBAUSATZ | Holder |
| K-FILTERELEMENT | Filter element |
| K-MANO NIPPEL | Nipples for pressure gauges |
| K-XV AGM 2 | Double nipples, parallel male thread |