

# K-VERTEILER HANSA

Manifolds

**HANSA FLEX**

## Lastnosti

|                     |                            |
|---------------------|----------------------------|
| vstopni tlak        | 0 - 16 bar                 |
| območje temperatur: | -10 °C to +50 °C           |
| Sredstva            | stisnjen zrak              |
| priključni navoj    | Material: Die-cast zinc    |
| ohišje              | Material: Grivory® (PA 66) |



## Navodilo

Drugi podatki na zahtevo.

## Artikel

| Opis           | Outlets                         | Navoj | pretok (L/min) | A (mm) | B        | C (mm) |
|----------------|---------------------------------|-------|----------------|--------|----------|--------|
| K- 07 25 11 17 | 3 x G 1/4                       | G 1/4 | 2700           | 52,0   | 65,5 mm  | 34,5   |
| K- 07 25 11 18 | 3 x G 1/4                       | G 3/8 | 3600           | 52,0   | 65,5 mm  | 34,5   |
| K- 07 25 11 19 | 2 x G 3/8, 1 x G 1/4, 1 x G 1/2 | G 3/8 | 7250           | 63,0   | 80,5 mm  | 43,0   |
| K- 07 25 11 20 | 2 x G 3/8, 1 x G 1/4, 1 x G 1/2 | G 1/2 | 7250           | 63,0   | 80,5 mm  | 43,0   |
| K- 07 25 11 21 | 2 x G 3/4                       | G 3/4 | 18000          | 85,0   | 109,5 mm | 58,5   |
| K- 07 25 11 22 | 2 x G 3/4                       | G 1   | 18000          | 85,0   | 109,5 mm | 58,5   |

## Nadomestni deli

|                              |                               |
|------------------------------|-------------------------------|
| K-HALTERBAUSATZ HANSA        | Holder HANSA                  |
| K-ERSATZBEHAELTER HANSA POLY | Spare tank HANSA polycarbonat |
| K-GERAETESTECKER             | Coupling socket               |