

K-FILTER INLINE

Filters

HANSA FLEX

Lastnosti

vstopni tlak Max. 18 bar


območje temperatur: 0 °C to +80 °C

finoča filtra 36,00 µm

filter Nickel-plated brass

ohišje Brass

drugi deli NBR



Navodilo

Drugi podatki na zahtevo.

Opis

For integration in a pneumatic system if different system
sections or tools require different air qualities.

Artikel

| Opis | Navoj | A (mm) | L (mm) | SW (mm) |
|----------------|-----------------------|-----------|-----------|------------|
| K- 07 25 05 72 | G 1/8 female/female | 16,0 | 36,0 | 17 |
| K- 07 25 05 73 | G 1/4 female/female | 18,0 | 41,0 | 19 |
| K- 07 25 05 74 | G 3/8 female / female | 22,0 | 53,0 | 24 |
| K- 07 25 05 75 | G 1/2 female/female | 28,4 | 62,0 | 30 |
| K- 07 25 05 76 | G 1/8 female/male | 16,0 | 36,0 | 17 |
| K- 07 25 05 77 | G 1/4 female/male | 18,0 | 41,0 | 19 |
| K- 07 25 05 78 | G 3/8 female / male | 22,0 | 53,0 | 24 |
| K- 07 25 05 79 | G 1/2 female/male | 28,4 | 62,0 | 30 |