

# K-FI PC-BEHÄLTER SCHUTZK MULTIFIX

Filters with polycarbonate bowl and bowl guard

**HANSA FLEX**

## Lastnosti

|   |  |
|---|--|
| <b>vstopni tlak</b>                       | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| <b>temperatura medija</b>                 | max. 60 °C   |
| <b>temperatura okolice</b>                | Max. 60 °C   |
| <b>velikost por v filtrirnem elementu</b> | 5 µm (BG 1 / BG 2), 40 µm (BG 3)                           |
| <b>ohišje</b>                             | Die-cast zinc, Aluminium for G 1 variant                   |
| <b>Drain valve</b>                        | Semi-automatic   |
| <b>meritev pretoka</b>                    | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar         |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Centrifugal separators with a sintered filter element.

## Artikel

| Opis           | Navoj | pretok (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Velikost |
|----------------|-------|----------------|--------|----------|--------|--------|----|----------|
| K- 07 25 00 48 | G 1/4 | 2100           | 47,8   | 152,1 mm | 27,0   | 125,1  | 6  | 1        |
| K- 07 25 00 51 | G 3/8 | 2100           | 47,8   | 152,1 mm | 27,0   | 125,1  | 10 | 1        |
| K- 07 25 00 54 | G 1/2 | 4000           | 68,8   | 181,8 mm | 34,5   | 147,3  | 15 | 2        |
| K- 07 25 00 57 | G 3/4 | 4000           | 68,8   | 181,8 mm | 34,5   | 147,3  | 20 | 2        |
| K- 07 25 00 60 | G 1   | 8000           | 100,0  | 305,8 mm | 52,0   | 253,8  | 25 | 3        |

## Nadomestni deli

|                                 |                           |
|---------------------------------|---------------------------|
| K-HALTERBAUSATZ MULTIFIX        | Holder                    |
| K-KOPPELPAKET MEHR              | Coupling packet           |
| K-KOPPELPAKET SCHMA             | Coupling packet           |
| K-METALLBEHÄLTER OELER MULTIFIX | Metal tank oiler          |
| K-PC-BEHÄLTER FILTER MULTIFIX   | Polycarbonate tank filter |
| K-SCHUTZKORB G                  | Protective cage           |
| K-FILTERELEMENT                 | Filter element            |
| K-AUTOMAT ABLASSVENTIL          | Automatic drain valve     |