

K-FI REGL METALLBEHAE S MANO MULTIF

Filter regulators with metal bowl and sight glass, incl. pressure gauge

HANSA FLEX

Lastnosti

| | |
|------------------------------------|--|
| vstopni tlak | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| temperatura medija | max. 60 °C |
| temperatura okolice | Max. 60 °C |
| velikost por v filtrirnem elementu | 5 µm (C55: 40 µm) |
| tesnilni material | NBR |
| vzmetni pokrov | POM-brass |
| ohišje | Die-cast zinc, Aluminium for G 1 variant |
| Drain valve | Semi-automatic |
| meritev pretoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



Navodilo

Drugi podatki na zahtevo.

Opis

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Navodila za naročanje

Filter regulators with bowl guard and metal bowl are also available with control ranges of 0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar. Please ask for more information. Lockable filter regulators available on request.

Artikel

| Opis | Navoj | regulacijsko območje | pretok (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Velikost |
|----------------|-------|----------------------|----------------|--------|----------|--------|--------|----|----------|
| K- 07 25 00 68 | G 1/4 | 0.5 - 10 bar | 1500 | 47,8 | 192,0 mm | 67,0 | 125,5 | 6 | 1 |
| K- 07 25 00 72 | G 3/8 | 0.5 - 10 bar | 1500 | 47,8 | 192,0 mm | 67,0 | 125,5 | 10 | 1 |
| K- 07 25 00 76 | G 1/2 | 0.5 - 10 bar | 3500 | 68,8 | 246,0 mm | 99,0 | 149,2 | 15 | 2 |
| K- 07 25 00 80 | G 3/4 | 0.5 - 10 bar | 3500 | 68,8 | 246,0 mm | 99,0 | 149,2 | 20 | 2 |
| K- 07 25 00 84 | G 1 | 0.5 - 10 bar | 12000 | 100,0 | 385,0 mm | 128,0 | 255,7 | 25 | 3 |

Nadomestni deli

| | |
|----------------------------------|---------------------------|
| K-HALTERBAUSATZ | Holder |
| K-SCHALTTAFELMUTTER | Nut |
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-SCHUTZKORB G | Protective cage |
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-FILTERELEMENT | Filter element |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |