


K-NEBELOELER PC-BEHAEALTER MULTIFIX

Oil-mist lubricators with polycarbonate bowl

HANSA FLEX

Lastnosti

vstopni tlak	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
temperatura medija	max. 60 °C
temperatura okolice	Max. 60 °C
tesnilni material	NBR
ohišje	Die-cast zinc, Aluminium for G 1 variant
kapalni nastavek	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve	Manual
vrsta olja	CL 32 acc. to DIN 51517 - ISO VG 32
meritev pretoka	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



Navodilo

Drugi podatki na zahtevo.

Opis

Proportional lubricators, oil can be filled under pressure.

Artikel

Opis	Navoj	pretok (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Velikost
K- 07 25 00 91	G 1/4	1900	47,8	167,8 mm	58,0	109,8	6	1
K- 07 25 00 94	G 3/8	1900	47,8	167,8 mm	58,0	109,8	10	1
K- 07 25 00 97	G 1/2	5000	68,8	198,2 mm	66,1	132,1	15	2
K- 07 25 01 00	G 3/4	5000	68,8	198,2 mm	66,1	132,1	20	2
K- 07 25 01 03	G 1	18000	100,0	324,3 mm	82,7	241,6	25	3

Nadomestni deli

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHAEALTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-TROPFAUFSATZ POLYCARBO 1	Drip attachment polycarbonate
K-TROPFAUFSATZ METALL	Drip attachment metal