


# K-NEBELOELER PC-BEHAEL S MULTIFIX

Oil-mist lubricators with polycarbonate bowl and bowl guard

**HANSA FLEX**

## Lastnosti

<b>vstopni tlak</b>	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
<b>temperatura medija</b>	max. 60 °C
<b>temperatura okolice</b>	Max. 60 °C
<b>tesnilni material</b>	NBR
<b>ohišje</b>	Die-cast zinc, Aluminium for G 1 variant
<b>kapalni nastavek</b>	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
<b>Drain valve</b>	Manual
<b>vrsta olja</b>	CL 32 acc. to DIN 51517 - ISO VG 32
<b>meritev pretoka</b>	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Navodilo

Drugi podatki na zahtevo.

## Opis

Proportional lubricators, oil can be filled under pressure.

## Artikel

Opis	Navoj	pretok (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Velikost
K- 07 25 00 93	G 1/4	1900	47,8	167,8 mm	58,0	109,8	6	1
K- 07 25 00 96	G 3/8	1900	47,8	167,8 mm	58,0	109,8	10	1
K- 07 25 00 99	G 1/2	5000	68,8	198,6 mm	66,1	132,5	15	2
K- 07 25 01 02	G 3/4	5000	68,8	198,6 mm	66,1	132,5	20	2
K- 07 25 01 05	G 1	18000	100,0	324,3 mm	82,7	241,6	25	3

## Nadomestni deli

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-TROPFAUFSATZ POLYCARBO 1	Drip attachment polycarbonate
K-TROPFAUFSATZ METALL	Drip attachment metal