

K-RD MULTIFIX

Non-return valves

HANSA FLEX

Lastnosti

| | |
|---------------------|----------------------------------------------------|
| vstopni tlak | Max. 16 bar |
| temperatura medija | max. 50 °C |
| temperatura okolice | Max. 50 °C |
| tesnilni material | NBR |
| ohišje | Die-cast zinc |
| meritev pretoka | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |
| tlak odprtja | Min. 0.1 bar |



Navodilo

Drugi podatki na zahtevo.

Opis

Spring-loaded seat valves.

Artikel

| Opis | Navoj | pretok (L/min) | A (mm) | B | C (mm) | D (mm) | Velikost |
|----------------|-------|-------------------|-----------|---------|-----------|-----------|----------|
| K- 07 25 11 77 | G 1/4 | 700 | 47,8 | 52,0 mm | 26,0 | 26,0 | 1 |
| K- 07 25 11 78 | G 3/8 | 700 | 47,8 | 52,0 mm | 26,0 | 26,0 | 1 |
| K- 07 25 11 79 | G 1/2 | 6000 | 68,8 | 67,0 mm | 33,5 | 33,5 | 2 |
| K- 07 25 11 80 | G 3/4 | 6000 | 68,8 | 67,0 mm | 33,5 | 33,5 | 2 |

Nadomestni deli

| | |
|---------------------|-----------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |