

K-NEBELOEL METALLBEHAEL MULTIFIX MI

Oil-mist lubricators with metal bowl and metal sight dome

HANSA FLEX

Lastnosti

| | |
|----------------------------|--|
| vstopni tlak | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| temperatura medija | max. 60 °C |
| temperatura okolice | Max. 60 °C |
| pretok | 1000 l/min |
| tesnilni material | NBR |
| ohišje | Die-cast zinc |
| kapalni nastavek | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl) |
| vrsta olja | CL 32 acc. to DIN 51517 - ISO VG 32 |
| meritev pretoka | At P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



Navodilo

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

Drugi podatki na zahtevo.

Opis

Micro-lubricators, oil can be filled under pressure.

Artikel

| Opis | Navoj | A (mm) | B | C (mm) | D (mm) | DN | Velikost |
|----------------|-------|--------|----------|--------|--------|----|----------|
| K- 07 25 00 88 | G 1/8 | 40,0 | 147,6 mm | 62,6 | 85,0 | 5 | 0 |
| K- 07 25 00 90 | G 1/4 | 40,0 | 147,6 mm | 62,6 | 85,0 | 5 | 0 |

Nadomestni deli

| | |
|------------------------------|--|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-ERSATZBEHAELTER MULTI MINI | Spare tank »multifix-mini« & »standard-mini« |
| K-TROPFAUFSATZ POLYCARBO 1 | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL | Drip attachment metal |