

# K-NEBELOELER METALLBEHAE T STANDARD

Oil-mist lubricators with metal bowl and metal sight dome

**HANSA FLEX**

## Lastnosti

<b>vstopni tlak</b>	Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
<b>temperatura medija</b>	max. 60 °C
<b>temperatura okolice</b>	Max. 60 °C
<b>tesnilni material</b>	NBR
<b>ohišje</b>	Die-cast zinc, painted silver
<b>kapalni nastavek</b>	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
<b>vrsta olja</b>	CL 32 acc. to DIN 51517 - ISO VG 32
<b>meritev pretoka</b>	At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
<b>drugi podatki</b>	User manual on request



## Opis

Proportional lubricators, oil can be filled under pressure.

## Artikel

Opis	Navoj	pretok (L/min)	A (mm)	C (mm)	D (mm)	DN
K- 07 25 08 88	G 1/4	1200	50,0	51,0	119,5	6
K- 07 25 08 91	G 3/8	1200	50,0	51,0	119,5	6
K- 07 25 08 94	G 3/8	2400	70,0	51,0	145,0	10
K- 07 25 08 97	G 1/2	4000	79,0	55,0	157,0	15
K- 07 25 09 00	G 3/4	9000	102,0	58,0	160,0	20
K- 07 25 09 03	G 1	9000	90,0	58,0	160,0	25
K- 07 25 09 06	G 1 1/4	9000	137,0	70,0	232,0	40
K- 07 25 09 09	G 1 1/2	9000	125,0	70,0	232,0	45

## Nadomestni deli

<b>K-HALTERBAUSATZ STANDARD</b>	Holder
<b>K-SCHUTZKORB G</b>	Protective cage
<b>K-TROPFAUFSATZ POLYCARBO</b>	Drip attachment polycarbonate
<b>K-XV AGM MS NI</b>	Double nipples, parallel male thread, nickel-plated brass
<b>K-RD NIPPEL MS NI</b>	Reducing nipples - nickel-plated brass
<b>K-LOESBARE DOPPELNIPPEL MS</b>	Double nipples
<b>K-TROPFAUFSATZ METALL</b>	Drip attachment metal