


K-NEBELOELER METALLBEHAE T STANDARD

Oil-mist lubricators with metal bowl and metal sight dome

HANSA FLEX

Lastnosti

| | |
|----------------------------|--|
| vstopni tlak | Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl) |
| temperatura medija | max. 60 °C |
| temperatura okolice | Max. 60 °C |
| tesnilni material | NBR |
| ohišje | Die-cast zinc, painted silver |
| kapalni nastavek | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl) |
| vrsta olja | CL 32 acc. to DIN 51517 - ISO VG 32 |
| meritev pretoka | At P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| drugi podatki | User manual on request |



Opis

Proportional lubricators, oil can be filled under pressure.

Artikel

| Opis | Navoj | pretok (L/min) | A (mm) | C (mm) | D (mm) | DN |
|----------------|---------|-------------------|-----------|-----------|-----------|----|
| K- 07 25 08 88 | G 1/4 | 1200 | 50,0 | 51,0 | 119,5 | 6 |
| K- 07 25 08 91 | G 3/8 | 1200 | 50,0 | 51,0 | 119,5 | 6 |
| K- 07 25 08 94 | G 3/8 | 2400 | 70,0 | 51,0 | 145,0 | 10 |
| K- 07 25 08 97 | G 1/2 | 4000 | 79,0 | 55,0 | 157,0 | 15 |
| K- 07 25 09 00 | G 3/4 | 9000 | 102,0 | 58,0 | 160,0 | 20 |
| K- 07 25 09 03 | G 1 | 9000 | 90,0 | 58,0 | 160,0 | 25 |
| K- 07 25 09 06 | G 1 1/4 | 9000 | 137,0 | 70,0 | 232,0 | 40 |
| K- 07 25 09 09 | G 1 1/2 | 9000 | 125,0 | 70,0 | 232,0 | 45 |

Nadomestni deli

| | |
|----------------------------|---|
| K-HALTERBAUSATZ STANDARD | Holder |
| K-SCHUTZKORB G | Protective cage |
| K-TROPFAUFSATZ POLYCARBO | Drip attachment polycarbonate |
| K-XV AGM MS NI | Double nipples, parallel male thread, nickel-plated brass |
| K-RD NIPPEL MS NI | Reducing nipples - nickel-plated brass |
| K-LOESBARE DOPPELNIPPEL MS | Double nipples |
| K-TROPFAUFSATZ METALL | Drip attachment metal |