

# K-WMV 3/2 MANU DREHHEBEL

3/2-way miniature valves, manually operated, with wing lever (2 positions)

**HANSA FLEX**

## Lastnosti

|                       |                     |
|-----------------------|---------------------|
| funkcija              | NC                  |
| Obratovalni tlak      | 0,5 - 10 bar        |
| delovna temperatura   | -10 °C do +60 °C    |
| pretok 6 bar in 5 bar | 35 NI/min           |
| nazivni Ø             | 2,5 mm              |
| sprožilni tlak 6 bar  | 8 N                 |
| ohišje ventila        | aluminij            |
| tlačni gumb           | ponikljana medenina |
| vzmet                 | nerjavno jeklo      |
| tesnilni material     | NBR                 |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Monostable (non-latching) and bistable (latching) versions available.

## Artikel

| Opis           | Priključek     | sporožitev |
|----------------|----------------|------------|
| K- 07 15 00 58 | 4 mm ob strani | monostable |
| K- 07 15 00 59 | M 5 ob strani  | monostable |
| K- 07 15 00 60 | 4 mm ob strani | bistabilno |
| K- 07 15 00 61 | M 5 ob strani  | bistabilno |