

# K-DRV ABLD SCHNVERSCHR C SCHLITZ

Unidirectional flow control valves, outgoing air restriction (»C«), quick-lock screw fitting

**HANSA FLEX**

## Lastnosti

|   |                                    |
|---|------------------------------------|
| Obratovalni tlak                              | maks. 10 bar                       |
| območje temperatur:                           | 0 °C to +70 °C                     |
| votli vijak, vrtljiva ročica, regulirni vijak | Nickel-plated brass                |
| notranji deli                                 | Brass with a bare metal surface    |
| tesnilo z zavihkom tesnilnega obroča          | NBR                                |
| tesnila (neizgubljiva)                        | Polyamide (glass fibre-reinforced) |



## Navodilo

Drugi podatki na zahtevo.

## Opis

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

## Artikel

| Opis           | C<br>(mm) | za cev        | Navoj | zev ključa | B<br>(mm) |
|----------------|-----------|---------------|-------|------------|-----------|
| K- 07 15 05 37 | 18,0      | 4 mm / 2,5 mm | M 5   | 8 mm       | 24,5      |
| K- 07 15 05 38 | 19,0      | 5 mm / 3 mm   | M 5   | 8 mm       | 24,5      |
| K- 07 15 05 39 | 19,0      | 6 mm / 4 mm   | M 5   | 8 mm       | 24,5      |
| K- 07 15 05 46 | 23,0      | 5 mm / 3 mm   | G 1/8 | 14 mm      | 32,0      |
| K- 07 15 05 47 | 25,0      | 6 mm / 4 mm   | G 1/8 | 14 mm      | 32,0      |
| K- 07 15 05 48 | 25,0      | 8 mm / 6 mm   | G 1/8 | 14 mm      | 32,0      |
| K- 07 15 05 43 | 26,5      | 6 mm / 4 mm   | G 1/4 | 17 mm      | 40,0      |
| K- 07 15 05 44 | 27,5      | 8 mm / 6 mm   | G 1/4 | 17 mm      | 40,0      |
| K- 07 15 05 42 | 28,5      | 10 mm / 8 mm  | G 1/4 | 17 mm      | 40,0      |
| K- 07 15 05 49 | 30,5      | 10 mm / 8 mm  | G 3/8 | 20 mm      | 50,0      |