

K-KDR SCHNVERSCHR

Mini pressure regulators, discharge port on thread, quick-lock screw fitting

HANSA FLEX

Lastnosti

| | |
|---|------------------------------------|
| regulacijsko območje | 0 - 8 bar |
| vstopni tlak | Max. 10 bar |
| območje temperatur: | 0 °C to +70 °C |
| votli vijak, vrtljiva ročica, regulirni vijak | Nickel-plated brass |
| notranji deli | Brass with a bare metal surface |
| tesnilo z zavhlkom tesnilnega obroča | NBR |
| tesnila (neizgubljiva) | Polyamide (glass fibre-reinforced) |



Navodilo

Drugi podatki na zahtevo.

Opis

Piston pressure regulator with self-relieving design, hollow bolt and pivoting ring piece. The regulator is screwed directly into the consumer (e.g. cylinder, handling equipment, etc.). The working pressure can thus be adapted to the specific application.

Artikel

| Opis | C (mm) | za cev | Navoj | zev ključa | B (mm) |
|----------------|-----------|--------------|-------|------------|-----------|
| K- 07 25 08 33 | 16,0 | G 1/8 IG | G 1/8 | 15 mm | 56,0 |
| K- 07 25 08 34 | 25,0 | 5 mm / 3 mm | G 1/8 | 15 mm | 56,0 |
| K- 07 25 08 35 | 25,0 | 6 mm / 4 mm | G 1/8 | 15 mm | 56,0 |
| K- 07 25 08 36 | 25,0 | 8 mm / 6 mm | G 1/8 | 15 mm | 56,0 |
| K- 07 25 08 31 | 26,5 | 6 mm / 4 mm | G 1/4 | 17 mm | 63,0 |
| K- 07 25 08 32 | 27,5 | 8 mm / 6 mm | G 1/4 | 17 mm | 63,0 |
| K- 07 25 08 30 | 28,5 | 10 mm / 8 mm | G 1/4 | 17 mm | 63,0 |