


K-MAGV MINI

Miniature solenoid valves 15 mm

HANSA FLEX

Lastnosti

| | |
|------------------------------------|---|
| Sredstva | Filtered, unlubricated compressed air |
| tlačno območje | 0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override |
| Priključek | In manifold base |
| območje temperatur: | -5 °C to +45 °C |
| čas odpiranja/čas zapiranja | 10 - 12 ms (depending on pressure) |
| moč tuljave | 2,5 W |
| Material: | umetna masa |
| tesnilni material | NBR, stainless steel |



Navodilo

Drugi podatki na zahtevo.

Opis

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikel

| Opis | funkcija | Napetost | Priključek | H (mm) | B (mm) |
|----------------|----------|----------|-----------------|-----------|-----------|
| K- 07 15 14 18 | NC | 24 V DC | Cable (30 cm) | 42,0 | 15,0 |
| K- 07 15 14 19 | NC | 24 V DC | for system plug | 42,0 | 15,0 |
| K- 07 15 14 20 | NC | 12 V DC | Cable (30 cm) | 42,0 | 15,0 |
| K- 07 15 14 21 | NC | 12 V DC | for system plug | 42,0 | 15,0 |
| K- 07 15 14 22 | NO | 24 V DC | Cable (30 cm) | 42,0 | 15,0 |
| K- 07 15 14 23 | NO | 24 V DC | for system plug | 42,0 | 15,0 |
| K- 07 15 14 24 | NO | 12 V DC | Cable (30 cm) | 42,0 | 15,0 |
| K- 07 15 14 25 | NO | 12 V DC | for system plug | 42,0 | 15,0 |