

K-PNEU LOGIKELEMENTE

Pneumatic logic elements

HANSA FLEX

Lastnosti

delovni tlak	OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
območje temperatur:	-10 °C to +60 °C
Priključek	Push-in fitting for 4 mm pipe
pretok	100 l/min (at 6 bar and $\Delta p = 1$ bar)
nazivni \varnothing	2,7 mm
ponastavitev	OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
Material:	Technopolymer
drsnik	Aluminium
tesnilni material	NBR



Navodilo

Drugi podatki na zahtevo.

Opis

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the Ω -rail (DIN EN 50022) integral with the body.

Artikel

Opis	funkcija	Višina (mm)	dolžina (mm)
K- 07 15 13 77	OR	40	38,5
K- 07 15 13 78	AND	40	38,5
K- 07 15 13 79	NOT	40	55,2
K- 07 15 13 80	YES	40	55,2
K- 07 15 13 81	MEMORY	41	89,5