

K-KURZH ZYL EINFACHW

Short-stroke cylinders, single-acting (magnetic)

HANSA FLEX

Lastnosti

Sredstva	Filtered compressed air, lubricated (ensure continuity) or unlubricated
Obratovalni tlak	maks. 10 bar
vklopni tlak	0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)
območje temperatur:	-10 °C to +80 °C
batnica	C45 steel, hard chrome-plated
cev	Aluminium alloy, anodised
premer glave	Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium
bat	Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE
tesnilo batnice	NBR (additional charge for PU and FKM)
tesnilo bata	NBR (additional charge for PU and FKM)



Navodilo

Drugi podatki na zahtevo.

Opis

Suitable for installation in limited spaces, with magnet.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Other types, e.g. increased thermal stability, non-standard strokes, through rod, non-rotating version, etc., available on request.

Artikel

Opis	Ø bata	Hod (mm)	Priključek	navoj znotraj batnica
K- 07 15 11 87	12 mm	10	M 5	M 3
K- 07 15 11 88	12 mm	25	M 5	M 3
K- 07 15 11 89	16 mm	10	M 5	M 5
K- 07 15 11 90	16 mm	25	M 5	M 5
K- 07 15 11 91	20 mm	10	M 5	M 5
K- 07 15 11 92	20 mm	25	M 5	M 5
K- 07 15 11 93	25 mm	10	G 1/8	M 5
K- 07 15 11 94	25 mm	25	G 1/8	M 5
K- 07 15 11 95	32 mm	10	G 1/8	M 6
K- 07 15 11 96	32 mm	25	G 1/8	M 6
K- 07 15 11 97	40 mm	10	G 1/8	M 6
K- 07 15 11 98	40 mm	25	G 1/8	M 6
K- 07 15 11 99	50 mm	25	G 1/8	M 8
K- 07 15 12 00	63 mm	25	G 1/8	M 8

Pribor

K-MAGNETSENSOREN-REED Reed magnetic sensor (incl. 2.5 m cable)