
K-STOPPVENTILE IG

Stop valves, ports 2 and 3 with female thread



Lastnosti					
delovni tlak	Max. 10 bar				
krmilni tlak	1 - 5 bar, depending on operating pressure				
temperatura medija	max. 70 °C				
Vgradna lega	Any. Ring pieces can still be rotated 360° after the valve has been tightened				
Material:	ponikljana medenina				
tesnilni material	Perbunan				





Navodilo

Drugi podatki na zahtevo.

Opis

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Artikel						
Opis	Port 1	Port 2	Priključek 3	B (mm)	C (mm)	
K- 07 15 20 46	G 1/8	G 1/8	G 1/8	52,0	21,0	
K- 07 15 20 45	G 1/4	G 1/4	G 1/8	58,0	25,0	
K- 07 15 20 47	G 3/8	G 3/8	G 1/8	63,0	31,0	
K- 07 15 20 44	G 1/2	G 1/2	G 1/8	72,0	40,0	