

K-WV 5/2 ELEKTROPNEUMATISCH

5/2-way pilot valves

HANSA FLEX

Lastnosti

Obratovalni tlak	2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\n vacuum up to 10 bar (external pilot air)
min. delovni tlak	2.5 bar (monostable), 1.0 bar (bistable)
območje temperatur:	-10 °C to +60 °C
pretok 6 bar in 10 bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
pretok 6 bar in 5 bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)



Navodilo

Drugi podatki na zahtevo.

Artikel

Opis	Priključek	Napetost	DN	funkcija	številka vezalne sheme	Krmiljenje
K- 07 15 01 93	G 1/8	24 V DC	5	5/2-way	35	
K- 07 15 01 94	G 1/4	24 V DC	8	5/2-way	35	
K- 07 15 25 81	G 3/8	24 V DC	13	5/2-way	35	
K- 07 15 01 95	G 1/2"	24 V DC	15	5/2-way	35	
K- 07 15 01 96	G 1/8	230 V, 50 Hz	5	5/2-way	35	
K- 07 15 01 97	G 1/4	230 V, 50 Hz	8	5/2-way	35	
K- 07 15 25 82	G 3/8	230 V, 50 Hz	13	5/2-way	35	
K- 07 15 01 98	G 1/2"	230 V, 50 Hz	15	5/2-way	35	
K- 07 15 01 99	G 1/8	24 V DC	5	5/2-way	36	
K- 07 15 02 00	G 1/4	24 V DC	8	5/2-way	36	
K- 07 15 25 83	G 3/8	24 V DC	13	5/2-way	36	
K- 07 15 02 01	G 1/2"	24 V DC	15	5/2-way	36	
K- 07 15 02 02	G 1/8	230 V, 50 Hz	5	5/2-way	36	
K- 07 15 02 03	G 1/4	230 V, 50 Hz	8	5/2-way	36	
K- 07 15 25 84	G 3/8	230 V, 50 Hz	13	5/2-way	36	
K- 07 15 02 04	G 1/2"	230 V, 50 Hz	15	5/2-way	36	