

# K-WV 5/2 DIFFERENZIALKOLBEN

5/2-way pilot valves, with differential piston

**HANSA FLEX**

## Lastnosti

|                        |  |
|------------------------|--|
| Obratovalni tlak       | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\n\nvacuum up to 10 bar (external pilot air) |
| min. delovni tlak      | 2.5 bar (monostable), 1.0 bar (bistable)   |
| območje temperatur:    | -10 °C to +60 °C   |
| pretok 6 bar in 10 bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)              |
| pretok 6 bar in 5 bar  | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)               |



## Navodilo

Drugi podatki na zahtevo.

## Artikel

| Opis           | Priključek | Napetost     | DN | funkcija | številka vezalne sheme | Krmiljenje |
|----------------|------------|--------------|----|----------|------------------------|------------|
| K- 07 15 02 05 | G 1/8      | 24 V DC      | 5  | 5/2-way  | 36                     |            |
| K- 07 15 02 06 | G 1/4      | 24 V DC      | 8  | 5/2-way  | 36                     |            |
| K- 07 15 25 85 | G 3/8      | 24 V DC      | 13 | 5/2-way  | 36                     |            |
| K- 07 15 02 07 | G 1/2"     | 24 V DC      | 15 | 5/2-way  | 36                     |            |
| K- 07 15 02 08 | G 1/8      | 230 V, 50 Hz | 5  | 5/2-way  | 36                     |            |
| K- 07 15 02 09 | G 1/4      | 230 V, 50 Hz | 8  | 5/2-way  | 36                     |            |
| K- 07 15 25 86 | G 3/8      | 230 V, 50 Hz | 13 | 5/2-way  | 36                     |            |
| K- 07 15 02 10 | G 1/2"     | 230 V, 50 Hz | 15 | 5/2-way  | 36                     |            |